

### PHARMA DEVILS

ENGINEERING DEPARTMENT

### STANDARD OPERATING PROCEDURE

**Department:** Engineering

Title: Specifications of Mixed Bed Unit

SOP No.	Revision No.	
<b>Effective Date</b>	Supersedes No.	
<b>Review Date</b>	Page No.	1 of 3

### 1.0 OBJECTIVE

The purpose of this SOP is:

**1.1** To describe the procedure for specifications of Mixed Bed Unit.

### 2.0 SCOPE

2.1 This SOP is applicable for the procedure for Specification of Mixed Bed Unit.

### 3.0 RESPONSIBILITY:

- **4.2** The Maintenance Engineer shall be responsible:
  - **4.2.1** Responsible for maintaining the specifications during replacement of resins.

### 4.0 ACCOUNTABILITY

Head -Engineering Services

### 5.0 PROCEDURE:

### **5.1 TYPES OF RESINS:**

- **5.1.1** Following are the specifications to be followed for selection of resins used in the Mixed Bed processing units.
  - 5.1.1.1 Cation Resin:
  - 5.1.1.2 Anion Resin:

### 5.2 MIXED BED RESINS:

**5.2.1** Make : M/S .....

**5.2.2** Type : MONO + 100S(NA+)

MONO + 600 S (CL-)

**5.2.3 Description:** This is a strong base anion exchange resin in bead form having benzyl ammonium groups and it is based on cross-linked polystyrene and has an isoporous structure. And it is based on



## PHARMA DEVILS

ENGINEERING DEPARTMENT

### STANDARD OPERATING PROCEDURE

**Department:** Engineering

Title: Specifications of Mixed Bed Unit

SOP No.	Revision No.	
<b>Effective Date</b>	Supersedes No.	
<b>Review Date</b>	Page No.	2 of 3

cross-linked polystyrene and has an isoporous structure. It has a very high basicity and is effective in removing silica and carbon dioxide. This grade is used for high quality de-ionized water.

**5.2.4** Physical form : Moist beads

**5.2.5** Wet screen grading : 0.3-1.2 mm

**5.2.6** Volume change : +9% (Chloride to Hydroxide form)

**5.2.7** Shipping weight :  $725 \text{kg/m}^3$ 

**5.2.8** Ionic form as supplied : Chloride

**5.2.9** Maximum operating temperature: 600C in hydroxide form and 900C in Chloride form.

**5.2.10** Operating pH range : 0-14

**5.2.11** Resistance to oxidizing agents : Chlorine should be absent

**5.2.12** Total Mixed Bed capacity : 60 kg CaCO<sub>3</sub>/m<sup>3</sup>

**5.2.13** Regenerant for regeneration : Sodium hydroxide, having the Concentration of 100% w/v.

### 5.3 ANALYSIS OF RESINS:

**5.3.1** Analysis of the Mixed Bed resins to be done in every year for its performance and efficiency. Such analysis reports to be kept preserved for maintaining history of resin.

### **6.0 ANNEXURES:**

Nil

### 8.0 References (S):

Nil

### 9.0 Glossary

SOP : Standard Operating procedure

No : Number

MCB : Mixed Column Base.



# PHARMA DEVILS

ENGINEERING DEPARTMENT

### STANDARD OPERATING PROCEDURE

**Department:** Engineering

Title: Specifications of Mixed Bed Unit

SOP No.	Revision No.	
<b>Effective Date</b>	Supersedes No.	
Review Date	Page No.	3 of 3

PLC : Programmable Logic Controller.

UV : Ultra Violet.

& : And.

% : Percentage.

V : Valve.