

PHARMA DEVILS PRODUCTION DEPARTMENT

Title: Cleaning of Inspection Belt Effective Date: Supersedes: Nil Review Date: Issue Date: Page No.: Purpose: To lay down operating procedure for the Cleaning of Inspection belt. Scope: This procedure is applicable to Responsibility: Production Chemist To supervise the activity Pre-operating Check: Check no material or residue of previous product is there. Frequency: At the complete batch or at the end of shift. Equipment used: Inspection belt. 2. Remove all the tablets or residue of previous product. 3. Start inspection belt or envious product. 3. Start inspection belt or remove the tablets or residue of previous product. 4. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. 5. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. 7. Remove the tablets or any residue of previous product from inspection Belt. 6. Mop the hopper and body with iPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with dry clean cloth. 8. Clean the surrounding area of inspection belt. 1.	Supersedes: Nil		SOP No.:	
Issue Date: Page No.: Purpose: To lay down operating procedure for the Cleaning of Inspection belt. Scope: This procedure is applicable to Responsibility: Production Chemist To supervise the activity Pre-operating Check: Check no material or residue of previous product is there. Frequency: At the complete batch or at the end of shift. Equipment used: Inspection belt Procedure for product change over: 1. Switch off the inspection belt. 2. Remove all the tablets or residue of previous product. 3. Start inspection belt to remove the tablets or residue of previous product. 4. Clean the inspection belt to remove the tablets or residue of previous product. 4. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. 5. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: 1. Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt.			Review Date:	
Purpose: To lay down operating procedure for the Cleaning of Inspection belt. Scope: This procedure is applicable to Responsibility: Production Chemist To supervise the activity Pre-operating Check: Check no material or residue of previous product is there. Frequency: At the complete batch or at the end of shift. Equipment used: Inspection belt Procedure for product change over: 1. Switch off the inspection belt. 2. Remove all the tablets or residue of previous product. 3. Start inspection belt to remove the tablets or residue of previous product. 4. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. 5. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. A. Procedure for the same product or at the end of shift: 1. Remove the tablets or any residue of previous product from inspection Belt.				
Scope: This procedure is applicable to Responsibility: Production Chemist To supervise the activity Pre-operating Check: Check no material or residue of previous product is there. Frequency: At the complete batch or at the end of shift. Equipment used: Inspection belt Procedure for product change over: 1. Switch off the inspection belt. 2. Remove all the tablets or residue of previous product. 3. Start inspection belt to remove the tablets or residue of previous product. 4. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. 5. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: 1. Remove the tablets or any residue of previous product from inspection Belt.				
Responsibility: Production Chemist To supervise the activity Pre-operating Check: Check no material or residue of previous product is there. Frequency: At the complete batch or at the end of shift. Equipment used: Inspection belt Procedure for product change over: 1. Switch off the inspection belt. 2. Remove all the tablets or residue of previous product. 3. Start inspection belt to remove the tablets or residue of previous product. 4. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. 5. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: 1. Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt.	Purpose:	To lay down operating procedure for the	Cleaning of Inspection belt.	
To supervise the activity Pre-operating Check: Check no material or residue of previous product is there. Frequency: At the complete batch or at the end of shift. Equipment used: Inspection belt Procedure for product change over: 1. Switch off the inspection belt. 2. Remove all the tablets or residue of previous product. 3. Start inspection belt to remove the tablets or residue of previous product. 4. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. 5. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: 1. 1. Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt.	Scope:	This procedure is applicable to		
 Frequency: At the complete batch or at the end of shift. Equipment used: Inspection belt Procedure for product change over: Switch off the inspection belt. Remove all the tablets or residue of previous product. Start inspection belt to remove the tablets or residue of previous product. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt. 	Responsibility:			
 Equipment used: Inspection belt Procedure for product change over: Switch off the inspection belt. Remove all the tablets or residue of previous product. Start inspection belt to remove the tablets or residue of previous product. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt. 	Pre-operating Che	ck: Check no material or residue of previous	s product is there.	
 Procedure for product change over: Switch off the inspection belt. Remove all the tablets or residue of previous product. Start inspection belt to remove the tablets or residue of previous product. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt. 	Frequency:	At the complete batch or at the end of shift.		
 Switch off the inspection belt. Remove all the tablets or residue of previous product. Start inspection belt to remove the tablets or residue of previous product. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt. 	Equipment used:	Inspection belt		
 Remove all the tablets or residue of previous product. Start inspection belt to remove the tablets or residue of previous product. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt. 	Procedure for pro	duct change over:		
 Remove all the tablets or residue of previous product. Start inspection belt to remove the tablets or residue of previous product. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt. 	1.	Switch off the inspection belt.		
 4. Clean the inspection belt with IPA wetted cloth followed by dry clean cloth. 5. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt. 	2.			
 5. Mop the hopper and body with IPA wetted cloth followed by dry clean cloth. Als the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt. 	3.	Start inspection belt to remove the tablets	or residue of previous product.	
 the surrounding area of inspection belt with wet cloth. Procedure for the same product or at the end of shift: Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt. 		-		
 Remove the tablets or any residue of previous product from inspection Belt. Clean the surrounding area of inspection belt. 	5.			
Belt. Clean the surrounding area of inspection belt.	Procedure for the	same product or at the end of shift:		
	1.	· · · ·		
	2.			